



ASBESTOS DISPOSAL INFORMATION

(Revised 07/02/)

The FNSB Solid Waste Division accepts asbestos on a scheduled basis. Please see the following information and instructions.

1. DAYS / TIMES ACCEPTED:

- First & Third Thursdays of the month from 9:00 – 11:30 a.m. & 1:30-3:30 p.m.
- Waste Shipment Manifest approval required prior to disposal.
- Missed appointments will need to be rescheduled.

2. PACKAGING:

- Friable asbestos waste must be properly packaged and appropriately labeled per applicable Federal and State of Alaska regulations (Anchorage EPA: 907-271-1485).
- Non-Friable loads must be completely wet prior to off-loading at the Solid Waste Facility.
- Metal pipe, etc., must be less than 8 feet in length.

3. FEES:

Asbestos generated from:

- Within the FNSB: Waste Shipment Manifest charge of \$1 .00 per ton.
- Outside the FNSB: Waste Shipment Manifest charge of \$2 .00 per ton.
- Outside the FNSB/over 25 tons per month: complete the “Request To Use Solid Waste Facilities” form & print from the Internet at <http://fnsb.us>, *Borough Functions, Solid Waste and Transfer Sites, Forms & Documents*
- Waste Shipment Manifest load charge of \$50/each; a \$200 flat rate fee for customer-caused asbestos discrepancies.
- Payment or use of approved charge account required at time of disposal.
- Fees are effective July 1, 20 - June 30, 20 .

4. PROCEDURES:

- Complete Items 1 through 8.
- Fax to FNSB Solid Waste Division at 907-459-1017.
- Manifests are reviewed for completeness, appointment scheduled, and then returned.
- On the **original manifest(s)**, complete Item 9, and Transporter Section (if applicable).
- **Original manifest(s)** must accompany **each** load.



Waste Shipment Manifest Instructions

WASTE GENERATOR SECTION (ITEMS 1-9)

1. Enter the name of the facility at which asbestos waste is generated and the address where the facility is located. In the appropriate spaces, enter the name of the owner of the facility and the owner's phone number.
2. Enter the name and address of the **Abatement Operator (Contractor)** performing the asbestos removal. In the appropriate spaces, enter their phone and fax number.
3. N/A - Information already entered
4. N/A - Information already entered
5. Indicate the types of asbestos waste materials generated:
6. Enter the number and type of containers checked in Item 5. See codes below:
 - DM – Metal drums
 - DP – Poly drums
 - BA – 6 mil. Plastic bags or wrapping
 - _____ – Other
7. Enter the total cubic yards of material in all shipping containers listed in Item 6.
8. Use this space for additional information or to request a disposal date.
9. To be completed by the **Abatement Operator (Contractor)**.

TRANSPORTER SECTION

- 10 & 11. To be completed by Transporter(s).

DISPOSAL SITE SECTION

- 12 & 13. N/A - Completed by the FNSB Solid Waste Division.

NOTE: Upon disposal, the original manifest will be retained by the **FNSB Solid Waste Division** and a copy will be given or mailed to the **Abatement Operator (Contractor)**.

WASTE SHIPMENT MANIFEST
 FAIRBANKS NORTH STAR BOROUGH
 SOLID WASTE DIVISION

FOR OFFICE USE	DATE APPROVED:
	DISPOSAL DATE:
	TIME: 9-11:30am/1:30-3:30pm
	<i>A MISSED APPOINTMENT IS REQUIRED TO BE RESCHEDULED.</i>

◆ GENERATOR

For Office Use Only	1. Work Site Name & Mailing Address:		Owner's Name:	Owner's Telephone #:							
	2. Abatement Operator (Contractor's) Name & Mailing Address:			Operator's Telephone # : _____							
				Email: _____ <i>(we may scan and return by email)</i>							
				Fax # : _____							
	3. Waste Disposal Site Name and Mailing Address: FNSB Solid Waste Division 455 Sanduri Street, Fairbanks, AK 99701			Telephone #: (907) 459-1482 phone (907) 459-1017 fax							
	4. Name and Mailing Address of Responsible Agency: Asbestos NESHAP Coordinator US EPA, Region 10 (OCE-127) 1200 Sixth Ave., Suite 900 Seattle, WA 98101			Agency Telephone #: (907) 271-1485							
	5. Type of Materials: <input type="checkbox"/> Friable <input type="checkbox"/> Non-Friable		6. Number and Type of Containers:		7. Total Cubic Yards of Material in Shipping Containers						
			<table border="1"> <thead> <tr> <th>No.</th> <th>Type</th> </tr> </thead> <tbody> <tr> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> </tr> </tbody> </table>		No.	Type					
No.	Type										
8. Special Handling Instructions, Additional Information, or to Request a Disposal Date:											
9. Abatement Operator's (Contractor's) Certification: I hereby declare that the contents of this consignment are fully and accurately described above by proper shipping name and are classified, packed, labeled, and are in all respects in proper condition for transportation by highway according to applicable International, Federal and State of Alaska regulations.											
Printed Name & Title		Signature		Month / Day / Year							

◆ TRANSPORTER

10. Transporter 1 (Acknowledgement of Receipt of Materials)		
Company Name, Address & Phone	Name and Title	Month / Day / Year
	Signature	
11. Transporter 2 (Acknowledgement of Receipt of Materials)		
Company Name, Address & Phone	Name and Title	Month / Day / Year
	Signature	

◆ DISPOSAL SITE

12. Discrepancy Indication Space: <input type="checkbox"/> None <input type="checkbox"/> Improperly Contained <input type="checkbox"/> Improper Labeling <input type="checkbox"/> Quantity		
13. Waste Disposal Site or Operator: Certification of receipt of asbestos materials covered by this manifest except as noted in Item 12.		
Name & Title	Signature	Month / Day / Year

ACM Regulations

Regulations divide ACM into two categories based on whether the material is friable or non-friable.

Friable ACM

Material that can be crumbled, pulverized, or reduced to powder by hand pressure. This typically includes products such as thermal or acoustic insulation and ceiling texture. The handling and disposal of friable ACM is stringently regulated as the material poses the greater health risk to residents and workers. Friable ACM is more commonly referred to as *regulated ACM* (RACM).

Non-friable ACM

Non-friable ACM, also referred to as non-regulated ACM (non-RACM), falls into one of two classifications:

- **Category I** – include packing, gaskets, resilient floor coverings, and asphalt roofing products that are not friable or likely to become friable during handling.
- **Category II** – include any other ACM that are not friable.

Despite the use of “non-regulated” to describe these materials, both state and federal regulations govern the handling and disposal of non-RACM. These less-stringent regulations apply as long as these materials are handled carefully during demolition or renovation to prevent the release of asbestos fibers. If these materials are damaged to the point that they may create dust or release asbestos fibers, they are regulated as RACM and must be removed, packaged, and disposed of accordingly.

Disposal of ACM Waste

The ADEC regulates the disposal of ACM, which may only be disposed of in a landfill permitted to accept it. This can include Class I and Class II municipal landfills, inert (construction and demolition) waste landfills, or asbestos landfills. However, each landfill determines its own acceptance policy. Most small rural landfills (Class III) are not permitted to accept any ACM. Contact the landfill directly to determine specific policies for ACM waste disposal or contact your ADEC regional office to discuss disposal options in the project area.

All RACM, including any non-RACM that has been damaged by processes that could result in the release of fibers, must be packaged in leak-tight containers or bags with proper warning labels and generator information. A waste shipment record signed by both the transporter and the landfill operator must accompany each load. In addition, the transporter must adhere to the Department of Transportation (DOT) hazardous materials requirements. Be sure to contact the landfill prior to the start of the project to discuss the landfills requirements for acceptance, handling, packaging, etc.

Disposal at the Landfill

RACM

The landfill operator is required to inspect each load to verify that the RACM is properly packaged and labeled and that waste shipment records match the quantities delivered. Any discrepancies in the waste shipment record must be reported to EPA. Access to the RACM disposal cell must be restricted with warning signs posted around the cell, and the landfill operator must supervise the disposal of each container to ensure that containment remains intact. One copy of the signed waste shipment record must be retained in the landfill record, and one returned to the waste generator. Detailed records of the quantities and disposal locations and depths of all RACM disposed in the landfill must also be kept in the landfill record.

Non-RACM

Non-RACM that has not been damaged does not require special packaging or shipment records, although the landfill can have specific requirements. Once at the landfill, non-RACM requires special handling to ensure that it does not become friable. This requires gently placing the material into the disposal cell so it does not break or create dust. Landfill equipment should be prevented from running over or compacting the non-RACM until it is covered by at least six inches of material that does not contain asbestos.

Landfills often choose to dispose of non-RACM separately from other waste because access restrictions also apply. These restrictions include prohibiting salvaging in any cell that accepts non-RACM to protect the public from contacting asbestos fibers. Landfills are not required to track waste shipment records or disposal quantities for non-RACM unless they are commingled with RACM and are therefore disposed in the RACM cell.

Summary of ACM Handling Requirements

	GENERATORS MUST	LANDFILLS MUST
ACM	<ul style="list-style-type: none"> Perform surveys and testing Notify EPA & AKOSH, as required Ensure removal is performed by certified asbestos abatement professionals only Use proper removal and safety techniques Handle materials so they are not crushed, broken, abraded, or otherwise may release fibers Determine landfill acceptance policies Deliver to a landfill permitted for asbestos disposal 	<ul style="list-style-type: none"> Ensure that ACM from demolitions and renovations is properly identified when delivered. ADEC recommends requiring submittal of building surveys for a project to identify if ACM is present, and disposal records if ACM is disposed elsewhere. Place all ACM at the appropriate working face in a manner that does not create breakage or dust Cover ACM daily with at least six inches of soil or non-ACM Do not allow salvaging in any area with ACM
Also for RACM	<ul style="list-style-type: none"> Seal RACM in leak-proof containers Apply required warning label Label with generator information Fill out all required shipping records Maintain all required records 	<ul style="list-style-type: none"> Inspect each load to verify that RACM waste is properly contained and labeled Ensure that shipping records are complete and match the amounts delivered and report any discrepancies to EPA Track quantities, depths, and location of all RACM waste Maintain access control and signage

Summary

ACM must be handled and disposed of appropriately to prevent exposure. Use the contacts below for any questions regarding your project.

Asbestos Regulatory Contacts

Agency	Issue	Phone
EPA	Removal, Reporting, & Demolition	(907) 271-3688
AKOSH	Removal, Handling, & Training	(800) 656-4972
AKOSH	Workplace Compliance & Enforcement	(800) 770-4940
ADEC	Disposal Options & Requirements	(907) 269-7622

ADEC Regional Office Contact

Anchorage

555 Cordova Street
Anchorage, AK 99501
(907) 269-7802

Fairbanks

610 University Avenue
Fairbanks, AK 99709
(907) 451-2108

Juneau

410 Willoughby Avenue, Suite 303
Juneau, AK 99801
(907) 465-5318